

China

BT01

Bythai Scaffolding

Excellent Corrosion Resistance Galvanised Scaffold Tube 3.2mm Thickness EN39 Standard

Basic Information

- Place of Origin:
- Brand Name:
- Certification: SGS
- Model Number:
- Price: \$5-\$18
- Packaging Details: In bundles
- Delivery Time: 7-15 days
- Payment Terms: TT/LC
- Supply Ability: 1000tons per month



Product Specification

Highlight:	Corrosion Resistant Galvanised Scaffold Tube, 3.2mm Thickness Galvanised Scaffold Tube.
Weight:	6.4kg/m
Corrosion Resistance:	Excellent
Standard:	EN39
Surface Treatment:	Galvanised
Tensile Strength:	420N/mm2
Thickness:	3.2mm
Bending Radius:	>2.5D
• Diameter:	48.3mm



More Images



EN39 Galvanized Scaffolding Tube

Product Description:

Galvanised Scaffold Tube is made of high-quality galvanised steel, complying with EN39 standard and with a thickness of 3.2mm. The surface of the tube is treated with galvanised process to ensure its durability and corrosion resistance. This tube also possesses excellent elongation properties of more than 20%. With its high-strength and anti-corrosion properties, Galvanised Scaffold Tube is well-suited for use in scaffolding structures, making it ideal for commercial and residential construction projects. Highly durable and long-lasting, it is an excellent choice for both indoor and outdoor applications.

Features:

Product Name: Galvanised Steel Scaffold Tube Standard: EN39 Weight: 6.4kg/m Name: Galvanised Scaffolding Tube Tensile Strength: 420N/mm2 Corrosion Resistance: Excellent Material: Galvanised Metal Scaffold Tube

Technical Parameters:

Name	Parameter
Material	Galvanised Steel
Yield Strength	245N/mm2
Weight	6.4kg/m
Elongation	>20%
Bending Radius	>2.5D
Length	6m
Diameter	48.3mm
Surface Treatment	Galvanised
Application	Scaffolding

Applications:

Bythai Scaffolding's galvanised scaffold tube, model BT01, is designed and manufactured in China, certified by SGS and priced from \$5 to \$18 per bundle. Delivery time is 7-15 days and payment terms are TT/LC. The company has the supply ability of 1000 tons per month. The elongation rate is more than 20%, and the yield strength is 245N/mm2. The standard of BT01 is EN39 and thickness is 3.2mm. BT01 is mainly used for scaffolding.

Support and Services:

Galvanised Scaffold Tube Technical Support and Service

We offer excellent technical support and service for our Galvanised Scaffold Tube products. Our experienced customer support team is available to answer any questions you have regarding installation, operation, or maintenance.

For more technical assistance, our in-house experts can provide detailed information about the product and provide advice on how to best use it. Our experts are also available for on-site consultations, if needed.

We also offer a wide range of after-sales services, such as maintenance, repairs, and servicing. Our experienced technicians are available to help you keep your product running smoothly.

For any inquiries regarding our Galvanised Scaffold Tube products, please contact us directly. We look forward to helping you get the most out of your purchase.

Packing and Shipping:

The packaging and shipping of Galvanised Scaffold Tube is as follows:

The tubes are packaged in bundles of 25, in cardboard boxes labelled with their specifications and measurements. The bundles are then wrapped in plastic and placed in wooden crates for secure shipping. The crates are then loaded onto a flatbed truck or rail car and transported to the destination. The tubes can also be shipped via air freight, depending on the customer's needs.

